PORTABLE PHOTOVOLTAIC PANEL YOLCO ZS200W



PRODUCT DESCTRIPTION
• Photovoltaic panel designed for use with Yolco portable refrigerators equipped with a solar charging socket.
• High efficiency (up to 24%) thanks to the use of monocrystalline panel cells.
• Laminated panel surface ensures resistance to dust, scratches and accidental splashes.
• Splash-proof cover with handle and cable pocket for safe storage and convenient transport.
• Integrated supports allow to tilt the panel towards the sun.

SPECIFICATION:
• Cell type: monocrystalline
• Number of cells: 36
• Efficiency: up to 24%*
• Rated power (Wp): 200W
• Power tolerance: +/-5%
• Rated voltage: 18V
• Rated current: 11.11A
• Open circuit voltage: 21.6V
• Short circuit current (Isc): 12.22A
• Maximum system voltage (DC): 700V
• Operating temperature range: -20°C ~ +75°C
• Ingress protection: IP65
• Dimensions (folded / unfolded): 635 x 565 mm / 2387 x 565 mm (25.0 x 22.2 in /94.0 x 22.2 in)
• Net weight: 8.9 kg (19.6 lb)

* STC: AM= 1.5kPa, T=25°C, irradiance 1000W/m2
NOCT: 48°C (+/-2°C)

CONTENTS OF THE PACKAGE:
• Photovoltaic panel
• Connection cables
• DC plug set
• Safety cover
• User manual



MODEL	ZS200W
Single item dimension (including package)	67,5(W) x 59(H) x 9cm(D)
Weight of single item (including package)	9,65kg
Material	-
Available colours	-
Quantity in master carton	2
Dimention of master carton	61(W) x 69,5(H) x 20,6cm(D)
Weight of master carton	20,58kg
Quantity on europalette (180x120x80)	-

ZS200W

5 902721 196138

EAN code: 5902721196138

www.arkas.pl • www.yolco.pl
ARKAS Sp. z o.o. ul. Kuziennicza 4, 59-400 Jawor, Polska, tel: +48 76 871-19-74, fax: +48 76 870-21-45, e-mail: dzialhandlowy@arkas.pl